SAFETY, ENVIRONMENTAL, AND REGULATORY INFORMATION

PCIe-5764

16-Bit, 1 GS/s, 4-Channel PCI FlexRIO Digitizer Device

Read this document and the documents listed in the additional resources section about installation, configuration, and operation of this equipment before you install, configure, operate, or maintain this product. Users are required to familiarize themselves with installation and wiring instructions in addition to requirements of all applicable codes, laws, and standards.

Regulatory Icons



-Notice-Take precautions to avoid data loss, loss of signal integrity, degradation of performance, or damage to the model.

—Caution—Take precautions to avoid injury. Consult the model documentation for cautionary statements when you see this icon printed on the model. Cautionary statements are localized into French for C-UL certification.



-Warning-Take precautions to avoid electrical shock.

Safety



Caution Observe all instructions and cautions in the user documentation. Using the model in a manner not specified can damage the model and compromise the built-in safety protection. Return damaged models to NI for repair.



Attention Suivez toutes les instructions et respectez toutes les mises en garde de la documentation utilisateur. L'utilisation d'un modèle de toute autre façon que celle spécifiée risque de l'endommager et de compromettre la protection de sécurité intégrée. Renvoyez les modèles endommagés à NI pour réparation.

Safety Voltage and Frequency

Notice The protection provided by the PCIe-5764 can be impaired if it is used in a manner not described in the user documentation.

| Maximum input voltage | ±2 V |
|-----------------------|---------|
| Frequency | 1.3 GHz |

Safety Standards

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- · UL 61010-1, CSA C22.2 No. 61010-1

EMC Guidelines

This product was tested and complies with the regulatory requirements and limits for electromagnetic compatibility (EMC) stated in the product specifications. These requirements and limits provide reasonable protection against harmful interference when the product is operated in the intended operational electromagnetic environment.

This product is intended for use in industrial locations. However, harmful interference may occur in some installations, when the product is connected to a peripheral device or test object, or if the product is used in residential or commercial areas. To minimize interference with radio and television reception and prevent unacceptable performance degradation, install and use this product in strict accordance with the instructions in the product documentation.

Furthermore, any changes or modifications to the product not expressly approved by NI could void your authority to operate it under your local regulatory rules.



Notice Operate this product only with shielded cables and accessories. Do not use unshielded cables or accessories unless they are installed in a shielded enclosure with properly designed and shielded input/output ports and connected to the product using a shielded cable. If unshielded cables or accessories are not properly installed and shielded, the EMC specifications for the product are no longer guaranteed.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- · EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- · EN 55011 (CISPR 11): Group 1, Class A emissions
- · AS/NZS CISPR 11: Group 1, Class A emissions



- · FCC 47 CFR Part 15B: Class A emissions
- · ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia, and New Zealand (per CISPR 11), Class A equipment is intended for use only in heavy-industrial locations.



Note Group I equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations, certifications, and additional information, refer to the *Product Certifications and Declarations* section.

Maximum Power Requirements

| 112 V | JA |
|--------|-------|
| ±12 V | 5 A |
| +3.3 V | 4.5 A |

Physical Characteristics

| Weight (unloaded) | 990 g (35 oz) |
|-------------------|---|
| Dimensions | 12.6 cm × 26.3 cm × 4.0 cm (5 in. × 10.4 in. × 1.6 in.) |

Maintenance

Clean the hardware with a soft, nonmetallic brush. Make sure that the hardware is completely dry and free from contaminants before returning it to service.

Environmental Guidelines

Environmental Characteristics

| Temperature | and | Hum | าเสเรษ |
|-------------|-----|-----|--------|

| Temperature | |
|------------------|---------------------------|
| Operating | 0 °C to 45 °C |
| Storage | -20 °C to 70 °C |
| Humidity | |
| Operating | 10% to 90%, noncondensing |
| Storage | 5% to 95%, noncondensing |
| Pollution Degree | 2 |

Indoor use only

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the Minimize Our Environmental Impact web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)

EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法(中国 RoHS)

・ 中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令(RoHS)。 关于 National Instruments 中国 RoHS 合规性信息,请登录 ni.com/environment/rohs_china。 (For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

Environmental Standards

This product meets the requirements of the following environmental standards for electrical equipment.

- IEC 60068-2-1 Cold
- IEC 60068-2-2 Dry heat
- · IEC 60068-2-78 Damp heat (steady state)
- MIL-PRF-28800F
 - Low temperature limits for operation Class 3
 - High temperature limits for operation Class 4



Note To verify marine approval certification for a product, refer to the product label or visit ni.com/certification and search for the certificate.

CE Compliance C

This product meets the essential requirements of applicable European Directives, as follows:

- · 2014/35/EU; Low-Voltage Directive (safety)
- · 2014/30/EU; Electromagnetic Compatibility Directive (EMC)
- 2011/65/EU; Restriction of Hazardous Substances (RoHS)

Product Certifications and Declarations

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for NI products, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Additional Resources

Visit ni.com/manuals for more information about your model, including specifications, pinouts, and instructions for connecting, installing, and configuring your system

Refer to the Getting Started Guide for the PCIe-5764 at ni.com/manuals for information about how to begin using your PCIe-5764.

Worldwide Support and Services

The NI website is your complete resource for technical support. At ni.com/support, you have access to everything from troubleshooting and application development self-help resources to email and phone assistance from NI Application Engineers.

Visit ni.com/services for information about the services NI offers

Visit ni.com/register to register your NI product. Product registration facilitates technical support and ensures that you receive important information updates

NI corporate headquarters is located at 11500 North Mopac Expressway, Austin, Texas, 78759-3504. NI also has offices located around the world. For support in the United States, create your service request at ni.com/support or dial 1 866 ASK MYNI (275 6964). For support outside the United States, visit the Worldwide Offices section of ni.com/niglobal to access the branch office websites, which provide up-to-date contact information.

